

GENU-FLIP™KIT For Dual-Leg Tables

ITEM INFORMATION

Item#	Description	Recommended Max. Table Size	Starting At
GFLIP-24	Kit with two flip mechanisms and one shaft for placing bases on 24" center	36" x 36"	\$326
GFLIP-30	Kit with two flip mechanisms and one shaft for placing bases on 30" center	36" x 42"	\$326
GFLIP-36	Kit with two flip mechanisms and one shaft for placing bases on 36" center	36" x 48"	\$326
GFLIP-42	Kit with two flip mechanisms and one shaft for placing bases on 42" center	36" x 54"	\$326
GFLIP-48	Kit with two flip mechanisms and one shaft for placing bases on 48" center	36" x 60"	\$326
GFLIP-54	Kit with two flip mechanisms and one shaft for placing bases on 54" center	36" x 66"	\$326
GFLIP-60	Kit with two flip mechanisms and one shaft for placing bases on 60" center	36" x 72"	\$326



NOTE: Pricing is the additional cost to add this mechanism to a base. The table base(s) are not included in this pricing.

Specification Example for a typical 30" x 60" table:


Qty 1 GFLIP-48 Genu-Flip™ kit for a table with legs spaced 48" apart on center

> 101 2022 PA GF-LC 101 22" painted end bases, Genu-Flip™ mount,

2" locking casters

ADVANTAGES

- Access latch from either end of the top for a quick flip and roll
- Easy to install with surface mount and simple assembly
- Design allows plenty of room for electrical components
- Compact nesting minimizes storage space to only 4%" per table
- Positive lock in both the vertical and horizontal position
- · Secure from accidental release during use
- Shipped partially knocked down to reduce freight costs
- Fits any Valley Design End Base Series



- Storage Width
 - = Table width + (# of tables -1) x 2.25"
- Maximum Storage Width
 - = Table width + 6.75" (table 5 aligns w/ table 1)

ល
Ē
TI TI
Ē
٥
Ш

Qty 2

Body Material	Injection molded black reinforced nylon
Block Material	Extruded and machined aluminum
Latch Material	Extruded and machined aluminum
Pivot Pin Material	5/16" dia. solid steel
Connecting Shaft	¾" dia. steel tube
Screws	#12-8 x 1" PBS, black zinc, #3 Phillips head

Note: Order with applicable bases using designator -GF.

